

# PGDQ2.MH17180 - Marking and Labeling Systems - Component

## Marking and Labeling Systems - Component

[See General Information for Marking and Labeling Systems - Component](#)

### FRANZ BARTA GMBH

Pfeiffergasse 1  
1150 Wien, AUSTRIA

MH17180

Model No.	Application Surface	Max Temp (°C)	Min Temp (°C)	Indoor Use	Outdoor Use	Additional Conditions
<b>Pressure-sensitive printed labels.</b>						
<b>Impressal-Stabilat</b>						
	Acrylonitrile butadiene styrene	80	-35	X	X	-
	Alkyd paint	80	-35	X	X	-
	Polycarbonate	80	-35	X	X	-
	Polypropylene	80	-	X	-	-
	Styrene acrylonitrile	80	-35	X	X	-

Note: Application surfaces are smooth, flat, and rigid unless otherwise specified. Labels suitable for application to two or more plastic or painted surfaces are considered suitable for blends of those plastics or paints, with Conditions of Acceptability common to the individual components in the blend.

Marking: Company name and model designation.

Last Updated on 2016-04-30

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2022 UL LLC"